


EMC134

Redox/ORP Combination Electrode



This Redox/ORP combination electrode with gel electrolyte and plastic body features application in aquariums, water and waste water technology as well as in water treatment for swimming pools. The platinum rod features high mechanical stability. In addition to the version with plug head and separated cable connection, models with fixed cable are available.

Electrode shaft	plastic (black), Ø 12 mm
Immersion length	120 mm
Metal electrode	platinum rod Ø 0.8 mm, 5 mm length
Temperature range	-5...80 °C
Reference system	Ag/AgCl
Electrolyte	gel-filled (about 3 M KCl)
Diaphragm	2 ceramic frits
Pressure	< 6 bar
Electrical connection	<ul style="list-style-type: none"> ▪ S8 coaxial plug head with thread PG 13.5 ▪ S7 coaxial lab plug head ▪ fixed cable
Process connection	<ul style="list-style-type: none"> ▪ with the relevant configuration thread PG 13.5 at sensor head for direct mounting in housings ▪ installation vertically or laterally up to 30° from vertical

- Electrical connections of the sensor:
 - EMC134I: S8 coaxial plug head with thread PG 13.5; separate connection cable is required
 - EMC134-L: S7 coaxial lab plug head; separate connection cable is required
 - EMC134-K050-F-P: 5 m fixed cable, stripped ends, thread PG 13.5
 - EMC134....: standard model EMC134 (plug head; cable length [1 m, 2 m, 5 m, 10 m], special cable length, plug, thread PG 13.5 are available)
 - EMC134 (OEM): customer specially designed models (sensor length, OEM logo, ...)

- Accompanying plug head cable connections:
 - K43/2: coaxial cable, length 2 m with S7/S8 socket, without meter plug
 - K50/2: coaxial cable, length 2 m with S7/S8 socket and German DIN plug
 - K51/2: coaxial cable, length 2 m with S7/S8 socket and BNC plug